



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/790,496	03/01/2004	Ryuichi Iwamura	50T5713.02	9501
36738	7590	09/01/2009	EXAMINER	
ROGITZ & ASSOCIATES 750 B STREET SUITE 3120 SAN DIEGO, CA 92101				PHUNKULH, BOB A
ART UNIT		PAPER NUMBER		
2419				
			MAIL DATE	DELIVERY MODE
			09/01/2009	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.



UNITED STATES PATENT AND TRADEMARK OFFICE

Commissioner for Patents
United States Patent and Trademark Office
P.O. Box 1450
Alexandria, VA 22313-1450
www.uspto.gov

**BEFORE THE BOARD OF PATENT APPEALS
AND INTERFERENCES**

Application Number: 10/790,496
Filing Date: March 01, 2004
Appellant(s): IWAMURA, RYUICHI

JOHN L. ROGITZ
For Appellant

EXAMINER'S ANSWER

This is in response to the appeal brief filed 5/20/2009 appealing from the Office action mailed 5/11/2009.

(1) Real Party in Interest

A statement identifying by name the real party in interest is contained in the brief.

(2) Related Appeals and Interferences

The examiner is not aware of any related appeals, interferences, or judicial proceedings which will directly affect or be directly affected by or have a bearing on the Board's decision in the pending appeal.

(3) Status of Claims

The statement of the status of claims contained in the brief is correct.

(4) Status of Amendments After Final

The appellant's statement of the status of amendments after final rejection contained in the brief is correct.

(5) Summary of Claimed Subject Matter

The summary of claimed subject matter contained in the brief is correct.

(6) Grounds of Rejection to be Reviewed on Appeal

The appellant's statement of the grounds of rejection to be reviewed on appeal is correct.

(7) Claims Appendix

The copy of the appealed claims contained in the Appendix to the brief is correct.

(8) Evidence Relied Upon

2003/0140343 **FALVO et al.** 07-2003

(9) Grounds of Rejection

The following ground(s) of rejection are applicable to the appealed claims:

Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

Claims 1-25 are rejected under 35 U.S.C. 103(a) as being unpatentable over **FALVO et al.** (US 2003/0140343), hereinafter **FALVO**.

Regarding claim 1, **FALVO** discloses a home entertainment system, comprising:
at least one server configured for both wired and wireless communication (the combination of digital set top box/cable modem 335 and WLAN bridge 330 function as the server for display devices 310, 315, 320, 325, see figure 3); and
at least one component configured for communicating with the server along a wired path or configured for communicating with the server along a wireless path (the

display devices 320, 325 are connectable to WLAN bridge 330 via either twisted pair connection or via RF link, see figure 3, and paragraph 0048), the server and/or the component determining with path to use for communication based on the component preference (by default: display devices 325, 320 prefer twisted pair path, while display device 310, 315 prefer RF link, see figure 3).

FALVO fails to explicitly disclose that each of the display devices 310, 315, 320, 325 or TV are configured to communicate with the server via both wired path and RF path at any time.

FALVO, however, discloses that display devices 320, 325 are connected to WLAN 330 via twisted pair and the display devices are also support both HomeRF and 802.11b wireless protocol (see paragraph 0048).

Therefore, it would have been obvious to one having ordinary skill in the art at the time of invention was made to connect each devices with both HomeRF and twisted pair at any time in order to maintain reliable connection with server at all time while also providing mobility.

Regarding claim 2, **FALVO** discloses a respective address is associated with each path over which the component communicates (see paragraph 0079).

Regarding claim 3, **FALVO** discloses the addresses are IP addresses (see paragraph 0079).

Regarding claim 4, **FALVO** discloses the component is selected from the group of components consisting of: televisions and portable computers (see figure 3).

Regarding claim 5, **FALVO** discloses the component is a TV (see figure 3).

Regarding claim 6, **FALVO** discloses at least one of: the server, and component, determines which path to use for communication based at least in part on a component preference (as show in figure 3, display devices are connectable to WLAN Bridge 330 via wireless or RF link or twisted pair and communicating based on each preferred connection).

Regarding claim 9, **FALVO** discloses a method for communicating a home network, comprising:

determining that both a wired and a wireless path exist between the components (as show in figure 3, display devices 320, and 325 are connectable to WLAN Bridge 330 via twisted pair and , see paragraph 0048);

determining whether at least one of the components prefers a particular path and if so, communicating data over that path (by default: display devices 325, 320 prefer twisted pair path, while display device 310, 315 prefer RF link, see figure 3).

FALVO fails to explicitly disclose that WLAN bridge selects/determines which path to use for communication based at least in part on a bandwidth capability and based on at least part on an occupancy ratio.

As shown in figure 3, the display devices in the in home network 305 are connectable to WLAN Bridge 330 via wireless or RF link or twisted pair.

Therefore, it would have been obvious to one having ordinary skill in the art at the time of invention was made selects the path based on the bandwidth capacity of the link or occupancy ratio of the link in order to improve the system's performance where wireless connection may be more suitable for connection for the server is currently serving multiples twisted pair connections and available for wireless connection or the server may be serving multiple wireless connections and available for wired connection.

Regarding claim 10, **FALVO** discloses communicating simultaneously between the components using both paths (the WLAN Bridge is simultaneously connectable to a display device connected by twisted pair link and a second display device connected by RF link, see figure 3).

Regarding claim 11, **FALVO** discloses a respective address is associated with each path over which the component communicates (see paragraph 0079).

Regarding claim 12, **FALVO** discloses the addresses are IP addresses (IP address, see paragraph 0079).

Regarding claim 13, **FALVO** discloses at least one component is selected from the group of components consisting of: televisions, and portable computers (TV,

computers, see paragraph 0013).

Regarding claim 14, **FALVO** discloses the component is a TV (TV, see paragraph 0013).

Regarding claim 15, **FALVO** discloses at least one of: a server, and a component, determines which path to use for communication based at least in part on a component preference (as shown in figure 3, display devices are connectable to WLAN Bridge 330 via wireless or RF link or twisted pair).

Regarding claim 18, **FALVO** discloses a system for communicating between at least first and second components in a home network, comprising:

means for establishing a wired communication path between the components (802.3 10BASE-T interface, see figure 14);

means for establishing a wireless communication path between the components (RF PHY, see figure 4);

means for communicating data over a component-preferred path when a component-preferred path is indicated, the component-preferred path being selected from the wired and wireless communication paths (by default: display devices 325, 320 prefer twisted pair path, while display device 310, 315 prefer RF link, see figure 3).

FALVO fails to explicitly discloses that the server determining which path to use for communication based one of the component preference or bandwidth capability and the occupancy ratio.

FALVO, however, discloses that display devices 320, 325 are connected to WLAN 330 via twisted pair and the display devices are also support both HomeRF and 802.11b wireless protocol (see paragraph 0048).

Therefore, it would have been obvious to one having ordinary skill in the art at the time of invention was made selects the path based on the bandwidth capacity of the link or occupancy ratio of the link in order to improve the system's performance where wireless connection may be more suitable for connection for the server is currently serving multiples twisted pair connections and available for wireless connection or the server may be serving multiple wireless connections and available for wired connection.

Regarding claim 19, **FALVO** discloses a respective address is associated with each path (IP address, see paragraph 0079).

Regarding claim 20, **FALVO** discloses wherein the addresses are IP addresses (IP address, see paragraph 0079).

Regarding claim 21, **FALVO** discloses at least one component is selected from the group of components consisting of: televisions, and portable computers (TV,

computers, see figure 3 and paragraph 0013).

Regarding claim 22, **FALVO** discloses the component is a TV (see figure 3 and paragraph 0013).

Regarding claim 23, **FALVO** at least one of: a server, and a component, determines which path to use for communication based at least in part on a component preference (as shown in figure 3, display devices are connectable to WLAN Bridge 330 via wireless or RF link or twisted pair and communicating based on each preferred connection).

Regarding claims 7-8, 16-17, 24-25, **FALVO** fails to explicitly disclose that WLAN bridge selects/determines which path to use for communication based at least in part on a bandwidth capability and based on at least part on an occupancy ratio.

As shown in figure 3, the display devices in the in home network 305 are connectable to WLAN Bridge 330 via wireless or RF link or twisted pair.

Therefore, it would have been obvious to one having ordinary skill in the art at the time of invention was made selects the path based on the bandwidth capacity of the link or occupancy ratio of the link in order to improve the system's performance where wireless connection may be more suitable for connection for the server is currently serving multiples twisted pair connections and available for wireless connection or the server may be serving multiple wireless connections and available for wired connection.

(10) Response to Argument

Before responding to the applicant's argument, the examiner has made the following clarification in the above rejections. **FALVO** discloses WLAN Bridge 330 selecting the path based on component preference (by default: the prefer connection for display devices 320 and 325 are twisted pair connections and the prefer connection for display devices 310, 315 are wireless connections). And, **FALVO** fails to explicitly disclose each display device is connected to WLAN 330 via both wireless connection and wired connection at any time or the server determining which path to use for communication based one of the bandwidth capability and the occupancy ratio. Nevertheless, the reference and the ground for rejection remain intact.

Claim 1 Sub-Heading:

In paragraph 0048, **FALVO** discloses the following:

FIG. 3 shows a digital cable TV system 300 including an in-home network including wireless display (remote wireless) devices 310, 315 and wired display devices 320, 325 used to create reminder and intercom messages using a wireless local area network (WLAN) 330 that is bridged either to a cable modem within an STB 335 or a stand-alone cable modem (not shown) to allow access to the Internet 340. Data received from the Internet 340 is primarily routed from the cable modem in STB 335 to the display devices 310, 315, 320, 325 through the WLAN Bridge 330. The display devices 310, 315, 320, 325 support both HomeRF and 802.11b wireless protocols (emphasis added).

As cited above, **FALVO** discloses display devices 310, 315, 320, 325 supports both wired connection and wireless connection (802.11b or HomeRF wireless protocols). Also shown in figure 3, display device 320 and 325 are connected to WLAN

bridge 330 via twisted pair connections and display device 310 and 315 are connected to WLAN bridge 330 via wireless connection.

Although figure 3 shows display devices 320 and 325 are connected to WLAN Bridge 330 via twisted pair connection, they are also connected to WLAN Bridge 330 via RF connection since they are close proximity to the WLAN Bridge 330 and the devices 320 and 325 are capable of wireless connection. By default, the prefer connection for display devices 320 and 325 are twisted pair connections and the prefer connection for display devices 310, 315 are wireless connections. The obvious rejection was made because **FALVO** fails to explicitly disclose each display device is connected to WLAN 330 via both wireless connection and wired connection at any time.

For the second argument, the claim clearly cited that the server determining which path to use for communication based on at least one of: a component preference, a bandwidth capability, an occupancy ratio. In other word, the claim requires only one condition. Therefore **FALVO** discloses selecting the path based on the component preference. By default, the prefer connection for display devices 320 and 325 are twisted pair connections and the prefer connection for display devices 310, 315 are wireless connections.

Claim 9 Sub-heading

As cited above, **FALVO** discloses display devices 310, 315, 320, 325 supports both wired connection and wireless connection (802.11b or HomeRF wireless protocols). Also shown in figure 3, display device 320 and 325 are connected to WLAN

bridge 330 via twisted pair connections and display device 310 and 315 are connected to WLAN bridge 330 via wireless connection. Thus, **FALVO** discloses determining that both a wired and wireless path exists between the components.

Although figure 3 shows display devices 320 and 325 are connected to WLAN Bridge 330 via twisted pair connection, they are also connected to WLAN Bridge 330 via RF connection since they are close proximity to the WLAN Bridge 330 and the devices 320 and 325 are capable of wireless connection. By default, the prefer connection for display devices 320 and 325 are twisted pair connections and the prefer connection for display devices 310, 315 are wireless connections. Thus, **FALVO** discloses communicating data over the component prefers link.

The obvious rejection was made because **FALVO** fails to explicitly disclose that the server determining which path to use for communication based one of the bandwidth capability and the occupancy ratio.

FALVO, however, discloses that display devices 320, 325 are connected to WLAN 330 via twisted pair and the display devices are also support both HomeRF and 802.11b wireless protocol (see paragraph 0048).

Therefore, it would have been obvious to one having ordinary skill in the art at the time of invention was made selects the path based on the bandwidth capacity of the link or occupancy ratio of the link in order to improve the system's performance where wireless connection may be more suitable for a connection for the server is currently serving multiples twisted pair connections and available for wireless connection via RF-PHY interface or the wired connection may be more suitable for a connection for the

Art Unit: 2419

server may be serving multiple wireless connections and available for wired connection via 802.3 10Base-T interface (see figure 4).

Claim 18 Sub-heading

The applicant's argument is already addressed in combination of claims 1 and 9 responses (see above).

(11) Related Proceeding(s) Appendix

No decision rendered by a court or the Board is identified by the examiner in the Related Appeals and Interferences section of this examiner's answer.

For the above reasons, it is believed that the rejections should be sustained.

Respectfully submitted,

/BOB A PHUNKULH/
Primary Examiner, Art Unit 2419

Conferees:

/Chirag G Shah/
Supervisory Patent Examiner, Art Unit 2419

/Daniel J. Ryman/
Supervisory Patent Examiner, Art Unit 2419